

DESK2PROTECT SL

ensures safety in summer in harsh, damp and dirty environments

CasaFan 
SafeLine


COMMERCIAL USE

Certified in accordance with Machinery Directive 2006/42/EC, part 1 for commercial use.



IP54

dust protected
splash proof




DESK2PROTECT #303512

Housing, protective grille and frame with double corrosion protection coating in white, fan blade in seawater-resistant aluminium

- High-performance table/superstructure fan in all-metal industrial design.
- Ideal for use as a personal fan in production, storage and shipping.
- Easy to assemble on superstructures or frames.
- 3 speeds by using the encapsulated pressure switch. 2-pole ON/OFF switch.
- Vertical tilt adjustable in the range of 130°.
- Protective grille, housing, frame and base with double coat of corrosion protection paint, colour white.
- Stable, anti-tip base.
- Practical handle on the reverse of the protective grille.
- 2.5 m rubber sheathed cable H07RN-F G 3 1.0 mm² for high mechanical loads with IP54 Schuko plug.
- High-performance aluminium fan blade.
- Protection rating – IP54 splash-proof, insulation class I.

Product	Code No.	Colour housing/grille	Blade
DESK2PROTECT SL	303512	Double coat of corrosion protection paint, white	Aluminium

Technical details		Dimensions (mm)	
Power motor (W)	43	Fan grille Ø mm	350
Voltage (V/Hz)	220–240/~50	Fan blade Ø mm	303
Number of speeds	3		
Rpm min. -1	1,360 max.		
Weight (kg)	5.1		
Sound pressure (L _p -3 m) dB(A)	40.8		
Sound power (L _w) dB(A)	58.4		
Airflow max. (m ³ /h)*	2,250		
Service value (m ³ /min/W)	1.0		



Easy to assemble on trusses and superstructures.



2-pole ON/OFF switch and switch for the different speeds are underneath the rubber housing.



Ambient temperature - 10° to +42 °C. * measured in accordance with IEC 60879